



### **R.45 Sensor**

Low Frequency Sensor



# - ∅1.125 ->

## 1.580 .050 × 30°

#### **DESCRIPTION AND FEATURES**

The R.45 is a low frequency resonant AE sensor with very high sensitivity. With a resonant frequency of 20 kHz the sensor is ideal for monitoring AE activity in very large structures. The sensor features a rugged stainless steel cavity with a BNC connector on the side.

#### **APPLICATIONS**

The sensor can be used in any application requiring a resonant low frequency sensor. Typical applications include structural health monitoring of large concrete, steel and geologic structures. The can also be used for leak detection in pipes and tanks.

#### **OPERATING SPECIFICATIONS**

#### Dynamic

Peak Sensitivity, Ref V/(m/s)	85 dB
Operating Frequency Range	5-30 kHz
Resonant Frequency, Ref V/(m/s)	20 kHz
Directionality	+/-1.5 dB
Environmental	
Temperature Range45	5° to 150° C

**PRODUCT DATA SHEET** 

#### Physical


Dimensions	1.125"OD X 1.55"H
	28.6 mm OD X 40.6 mm H
Weight	121 grams
Case Material	Stainless Steel
Face Material	Ceramic
Connector	BNC
Connector Locations	Side

#### **ORDERING INFORMATION AND ACCESSORIES**

R.45	R.45
Cable (specify length in '-XX' m at end of PN)	1234-X
Magnetic Hold-Down	MHSTD
Pre-amplifier0/2/4, 2/	/4/6, 1220
Preamp to System Cable (specify length in 'm')	1234-X
Amplifier Subsystems A	E2A, AE5A

Sensors include

NIST Calibration Certificate & Warranty



 WORLDWIDE HEADQUARTERS:

 195 Clarksville Rd •

 Princeton Jct, NJ 08550 • USA

 T: +1.609.716.4000 • F: +1.609.716.0706

 E-MAIL: sales.systems@mistrasgroup.com

CANADA T: CHINA T: FRANCE T: GERMANY T: GREECE T:

T: +1.403.556.1350 T: +86.10.5877.3631 T: +331.498.26040 T: +49.040 2000.4025 T: +30.210.2846.801-4 
 HOLLAND
 T: +31.0

 INDIA
 T: +91.2

 JAPAN
 T: +81.3

 MALAYSIA
 T: +60.9

 MIDDLE EAST
 T: +973

T: +31.010.245.0325 T: +91.22.2586.2444 T: +81.33.498.3570 T: +60.9.517.3788 T: +973.17.729.356 RUSSIA SCANDINAVIA S. AMERICA UK

T: +7495.789.4549 T: +46(0)31.252040 T: +55.11.3082.5111 T: +44(0)1954.231.612